according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Opteon™ XP10 (R-513A) Refrigerant

SDS-Identcode : 130000051352

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Refrigerant

stance/Mixture

Recommended restrictions : For professional and industrial installation and use only.

on use

1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.

Baanhoekweg 22

3313 LA Dordrecht Netherlands

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person responsible for the SDS

: sds-support@chemours.com

#### 1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Gases under pressure, Liquefied gas H280: Contains gas under pressure; may explode if

heated.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

 $\Diamond$ 

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.05.2020

 7.0
 09.10.2020
 1336496-00046
 Date of first issue: 27.02.2017

Precautionary statements : Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

#### **Additional Labelling**

Contains fluorinated greenhouse gases. (HFC-134a)

#### 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
2,3,3,3-Tetrafluoropropene#	754-12-1	Flam. Gas 1B; H221	56
	468-710-7	Press. Gas Liquefied	
	01-0000019665-61	gas; H280	
1,1,1,2-Tetrafluoroethane#	811-97-2	Press. Gas Liquefied	44
	212-377-0	gas; H280	
	01-2119459374-33		

<sup>#</sup> Voluntarily-disclosed non-hazardous substance

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

area

Get medical attention immediately.

In case of eye contact : Get medical attention immediately.

If swallowed : Ingestion is not considered a potential route of exposure.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : May cause cardiac arrhythmia.

Other symptoms potentially related to misuse or inhalation

abuse are

Cardiac sensitisation Anaesthetic effects Light-headedness

Dizziness confusion

Lack of coordination

Drowsiness Unconsciousness

Skin contact may provoke the following symptoms:

Irritation

Swelling of tissue

Itching Discomfort Redness

Eye contact may provoke the following symptoms

tearing Redness Discomfort

Risks : Contact with liquid or refrigerated gas can cause cold burns

and frostbite.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Because of possible disturbances of cardiac rhythm, cate-

cholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with spe-

cial caution.

#### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Hydrogen fluoride Fluorine compounds Carbon oxides carbonyl fluoride

#### 5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

## 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow

preventative device in piping. Close valve after each use and

when empty.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid breathing gas.

Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

sessment

Wear cold insulating gloves/ face shield/ eye protection. Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet

piped to use point.

Use a check valve or trap in the discharge line to prevent haz-

ardous back flow into the cylinder. Prevent backflow into the gas tank.

Use a pressure reducing regulator when connecting cylinder

to lower pressure (<3000 psig) piping or systems.

Close valve after each use and when empty. Do NOT change

or force fit connections.

Prevent the intrusion of water into the gas tank.

Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders.

Use a suitable hand truck for cylinder movement. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in

accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides
Oxidizing agents
Flammable liquids

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 1336496-00046 Date of first issue: 27.02.2017 7.0 09.10.2020

> Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases **Explosives** 

Acutely toxic substances and mixtures

Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage tem- : < 52 °C

perature

age stability

Further information on stor- : The product has an indefinite shelf life when stored properly.

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
1,1,1,2-	811-97-2	TWA	1,000 ppm	GB EH40
Tetrafluoroethane			4,240 mg/m3	
	Further information: Where no specific short-term exposure limit is listed, a			
	figure three times the long-term exposure limit should be used.			

## Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
2,3,3,3- Tetrafluoropropene	Workers	Inhalation	Long-term systemic effects	950 mg/m3
1,1,1,2- Tetrafluoroethane	Workers	Inhalation	Long-term systemic effects	13936 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2476 mg/m3

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,3,3,3-Tetrafluoropropene	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	1.77 mg/kg dry
		weight (d.w.)
	Soil	1.54 mg/kg dry

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.05.2020

 7.0
 09.10.2020
 1336496-00046
 Date of first issue: 27.02.2017

		weight (d.w.)
	Marine water	0.01 mg/l
	Marine sediment	0.178 mg/kg dry weight (d.w.)
1,1,1,2-Tetrafluoroethane	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	0.75 mg/kg dry weight (d.w.)
	Sewage treatment plant	73 mg/l

#### 8.2 Exposure controls

#### **Engineering measures**

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

### Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

Face-shield

Equipment should conform to BS EN 166

Hand protection

Material : Low temperature resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change

gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to BS EN 14387

Filter type : Organic gas and low boiling vapour type (AX)

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

### **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : Liquefied gas

Colour : colourless

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Odour : slight, ether-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

-29.2 °C

Flash point : Not applicable

Evaporation rate : > 1

(CCL4=1.0)

Flammability (solid, gas) : Will not burn

Burning rate : 15 mm/s

Upper explosion limit / Upper

flammability limit

Upper flammability limit

Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit

Method: ASTM E681

None.

Vapour pressure : 7,063.6 hPa (25 °C)

Relative vapour density : 3.83

(Air = 1.0)

Relative density : 1.17 (25 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

#### 9.2 Other information

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.05.2020

 7.0
 09.10.2020
 1336496-00046
 Date of first issue: 27.02.2017

Particle size : Not applicable

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

#### 10.4 Conditions to avoid

Conditions to avoid : This substance is not flammable in air at temperatures up to

100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other

purposes.

Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.

Incompatible with acids and bases. Incompatible with oxidizing agents.

Oxygen Peroxides

peroxide compounds Powdered metals

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Information on likely routes of : Inhalation exposure Skin contact

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Eye contact

### **Acute toxicity**

Not classified based on available information.

#### **Components:**

#### 2,3,3,3-Tetrafluoropropene:

Acute inhalation toxicity : LC50 (Rat): > 405800 ppm

Exposure time: 4 h Test atmosphere: gas

Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 120000 ppm

Test atmosphere: gas

Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): >

120000 ppm

Test atmosphere: gas

Remarks: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m3

Test atmosphere: gas

Remarks: Cardiac sensitisation

## 1,1,1,2-Tetrafluoroethane:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm

Exposure time: 4 h Test atmosphere: gas

Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 40000 ppm

Test atmosphere: gas

Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): 80000

ppm

Test atmosphere: gas

Symptoms: May cause cardiac arrhythmia.

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m3

Test atmosphere: gas

Symptoms: May cause cardiac arrhythmia.

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

#### Skin corrosion/irritation

Not classified based on available information.

#### **Components:**

### 2,3,3,3-Tetrafluoropropene:

Result : No skin irritation

#### 1,1,1,2-Tetrafluoroethane:

Result : No skin irritation

## Serious eye damage/eye irritation

Not classified based on available information.

#### **Components:**

## 2,3,3,3-Tetrafluoropropene:

Result : No eye irritation

#### 1,1,1,2-Tetrafluoroethane:

Result : No eye irritation

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### **Components:**

#### 2,3,3,3-Tetrafluoropropene:

Exposure routes : Skin contact Result : negative

#### 1,1,1,2-Tetrafluoroethane:

Exposure routes : Skin contact Result : negative

Exposure routes : Inhalation Species : Rat Result : negative

Exposure routes : Inhalation Species : Humans Result : negative

## Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

#### **Components:**

## 2,3,3,3-Tetrafluoropropene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Test Type: In vivo mammalian alkaline comet assay

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 489

Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

#### 1,1,1,2-Tetrafluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Application Route: inhalation (gas) Method: OECD Test Guideline 486

Result: negative

Germ cell mutagenicity- As-

sessment

: Weight of evidence does not support classification as a germ

cell mutagen.

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

## 2,3,3,3-Tetrafluoropropene:

Result : negative

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

#### 1,1,1,2-Tetrafluoroethane:

Species : Rat

Application Route : inhalation (gas)

Exposure time : 2 Years

Method : OECD Test Guideline 453

Result : negative

Carcinogenicity - Assess-

ment

: Weight of evidence does not support classification as a car-

cinogen

#### Reproductive toxicity

Not classified based on available information.

#### **Components:**

#### 2,3,3,3-Tetrafluoropropene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

: Weight of evidence does not support classification for repro-

ductive toxicity, No effects on or via lactation

#### 1,1,1,2-Tetrafluoroethane:

Effects on fertility : Species: Mouse

Application Route: Inhalation

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rabbit

Application Route: inhalation (gas) Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

: Weight of evidence does not support classification for repro-

ductive toxicity

#### STOT - single exposure

Not classified based on available information.

#### **Components:**

### 2,3,3,3-Tetrafluoropropene:

Exposure routes : inhalation (gas)

Assessment : No significant health effects observed in animals at concentra-

tions of 20000 ppmV/4h or less

#### 1,1,1,2-Tetrafluoroethane:

Exposure routes : inhalation (gas)

Assessment : No significant health effects observed in animals at concentra-

tions of 20000 ppmV/4h or less

#### STOT - repeated exposure

Not classified based on available information.

#### Components:

## 2,3,3,3-Tetrafluoropropene:

Exposure routes : inhalation (gas)

Assessment : No significant health effects observed in animals at concentra-

tions of 250 ppmV/6h/d or less.

#### 1,1,1,2-Tetrafluoroethane:

Exposure routes : inhalation (gas)

Assessment : No significant health effects observed in animals at concentra-

tions of 250 ppmV/6h/d or less.

#### Repeated dose toxicity

#### Components:

#### 2,3,3,3-Tetrafluoropropene:

Species : Rat, male and female

NOAEL : 50000 ppm

LOAEL : >50000 ppm

Application Route : inhalation (gas)

Exposure time : 13 Weeks

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Method : OECD Test Guideline 413

1,1,1,2-Tetrafluoroethane:

Species : Rat, male and female

NOAEL : 50000 ppm LOAEL : >50000 ppm Application Route : inhalation (gas)

Exposure time : 2 yr

Method : OECD Test Guideline 453

### **Aspiration toxicity**

Not classified based on available information.

#### Components:

#### 2,3,3,3-Tetrafluoropropene:

No aspiration toxicity classification

#### 1,1,1,2-Tetrafluoroethane:

No aspiration toxicity classification

## **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

#### 2,3,3,3-Tetrafluoropropene:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): > 100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): > 75 mg/l

Exposure time: 3 d

Method: OECD Test Guideline 201

#### 1,1,1,2-Tetrafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l

Exposure time: 96 h

Method: Regulation (EC) No. 440/2008, Annex, C.1

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 980 mg/l

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

aquatic invertebrates Exposure time: 48 h

Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic : ErC50 (green algae): > 100 mg/l

plants Exposure time: 96 h

Remarks: Based on data from similar materials

#### 12.2 Persistence and degradability

#### **Components:**

#### 2,3,3,3-Tetrafluoropropene:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

1,1,1,2-Tetrafluoroethane:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

#### 12.3 Bioaccumulative potential

#### **Components:**

#### 2,3,3,3-Tetrafluoropropene:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2 (25 °C)

#### 1,1,1,2-Tetrafluoroethane:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

: log Pow: 1.06

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This mixture contains no substance considered to be persis-

tent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bio-

accumulating (vPvB)..

#### 12.6 Other adverse effects

## Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

#### **Product:**

100-year global warming potential: 631

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

### **SECTION 14: Transport information**

#### 14.1 UN number

IMDG

IATA

**ADN** UN 1078 In case a substance is inside a refrigerating machine is applied the following n° ONU: UN 2857

ADR UN 1078 In case a substance is inside a refrigerating machine is applied the following n° ONU: UN 2857

RID UN 1078 In case a substance is inside a refrigerating machine is applied the following n° ONU: UN 2857

IMDG
UN 1078 In case a substance is inside a refrigerating machine is applied the following n° ONU: UN 2857

IATA
UN 1078 In case a substance is inside a refrigerating machine is applied the following n° ONU: UN 2857

UN 1078 In case a substance is inside a refrigerating machine is applied the following n° ONU: UN 2857

## 14.2 UN proper shipping name

ADN : REFRIGERANT GAS, N.O.S. (2,3,3,3-Tetrafluoropropene, 1,1,1,2-Tetrafluoroethane)

In case a substance is inside a refrigerating machine the shipping name will be: REFRIGERATING MACHINES

ADR : REFRIGERANT GAS, N.O.S. (2,3,3,3-Tetrafluoropropene, 1,1,1,2-Tetrafluoroethane)

In case a substance is inside a refrigerating machine the shipping name will be: REFRIGERATING MACHINES

RID : REFRIGERANT GAS, N.O.S. (2,3,3,3-Tetrafluoropropene, 1,1,1,2-Tetrafluoroethane)

In case a substance is inside a refrigerating machine the shipping name will be: REFRIGERATING MACHINES

: REFRIGERANT GAS, N.O.S. (2,3,3,3-Tetrafluoropropene, 1,1,1,2-Tetrafluoroethane)

In case a substance is inside a refrigerating machine the shipping name will be: REFRIGERATING MACHINES

: Refrigerant gas, n.o.s. (2,3,3,3-Tetrafluoropropene, 1,1,1,2-Tetrafluoroethane)

In case a substance is inside a refrigerating machine the shipping name will be: REFRIGERATING MACHINES

Not permitted for transport

### 14.3 Transport hazard class(es)

 ADN
 : 2

 ADR
 : 2

 RID
 : 2

 IMDG
 : 2.2

IATA : 2.2

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Revision Date: Date of last issue: 05.05.2020 Version SDS Number: 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

## 14.4 Packing group

ADN

Packing group Not assigned by regulation

Classification Code 2A Hazard Identification Number : 20 Labels 2.2

ADR

Packing group Not assigned by regulation

Classification Code Hazard Identification Number: 20 Labels 2.2 Tunnel restriction code : (C/E)

RID

Packing group : Not assigned by regulation

. adming group Classification Code : 2A Hazard Identification Number : 20 Labels : 2.2 ((13))

IMDG

Packing group Not assigned by regulation

Labels 2.2 EmS Code F-C, S-V

IATA (Cargo)

Packing instruction (cargo 200

aircraft)

Packing group Not assigned by regulation Labels Non-flammable, non-toxic Gas

IATA (Passenger)

Packing instruction (passen- : 200

ger aircraft)

Not assigned by regulation Packing group Labels Non-flammable, non-toxic Gas

14.5 Environmental hazards

**ADN** 

Environmentally hazardous no

**ADR** 

Environmentally hazardous no

Environmentally hazardous no

**IMDG** 

Marine pollutant no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Remarks : Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

: Not applicable

''

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

### 15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

### **SECTION 16: Other information**

Other information : Opteon™ and any associated logos are trademarks or copy-

rights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The

Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or

nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical

lines.

**Full text of H-Statements** 

H221 : Flammable gas.

H280 : Contains gas under pressure; may explode if heated.

#### Full text of other abbreviations

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 05.05.2020 7.0 09.10.2020 1336496-00046 Date of first issue: 27.02.2017

Flam. Gas : Flammable gases
Press. Gas : Gases under pressure

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### **Further information**

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

Sheet cy, http://echa.europa.eu/

#### Classification of the mixture:

Classification procedure:

Press. Gas Liquefied gas H280 Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 1907/2006



## Opteon™ XP10 (R-513A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.05.2020

 7.0
 09.10.2020
 1336496-00046
 Date of first issue: 27.02.2017

Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB/EN